

CLG2030G-C

02

POWER TYPE
LPG

BASE CAPACITY
@RATED LOAD CENTER
6,000 LBS/2,750 KG

LOAD CENTER
24 IN/600 MM

SERVICE WEIGHT
10,527 LBS/4,785 KG



CLG2030G-C SPECIFICATIONS >>>

| | | CLG2030G-C | | | | | |
|------------------|-------------------------|--------------|------------------------------------|-----------------|------------------|-----------|-----------------|
| General | Model | | CLG2030G-C | | | | |
| | Power Type | 1 | LPG | | | | |
| | Units | 2 | Imperial | | Metric | | |
| | Base Capacity | 3 | @Rated load center | lbs | 6000 | kg | 2750 |
| | Load Center | 4 | | in | 24 | mm | 600 |
| Weights | Service Weight | 5 | Unloaded | lbs | 10527 | kg | 4785 |
| | Axle Load | 6 | Loaded/Unloaded,Front | lbs | 14421/2156 | kg | 6555/980 |
| | | 7 | Loaded/Unloaded,Rear | lbs | 4015/6512 | kg | 1825/2960 |
| Tires | Tire Type | 8 | Cushion | | | | |
| | Wheels | 9 | Front/Rear | | | | |
| | Wheelbase | 10 | | in | 58.5 | mm | 1485 |
| | Tire Size | 11 | Front | | 21x8-15 | | |
| | | 12 | Rear | | 16x5x10-1/2 | | |
| | Tread Width | 13 | Front/Rear | in | 35.8/36.2 | mm | 910/920 |
| Mast | Max.Fork Height | 14 | Std 3-stage mast | in | 185 | mm | 4700 |
| | Free lift | 15 | Std 3-stage mast | in | 40.7 | mm | 1033 |
| | Height,Upright Lowered | 16 | Std 3-stage mast | in | 85.8 | mm | 2180 |
| | Height,Upright Extended | 17 | Std 3-stage mast | in | 231.7 | mm | 5886 |
| | Mast Tilt,Fwd/Back | 18 | Std 3-stage mast | ° | 6 / 6 | | |
| | Carriage | 19 | Width | in | 43.3 | mm | 1100 |
| | Fork Spread | 20 | Minimum/Maximum | in | 9.6/43.3 | mm | 244/1100 |
| | Fork Dimensions | 21 | TxWxL | in | 1.8 x 4.8 x 42.1 | mm | 45 x 122 x 1070 |
| Chassis | Length to Fork Face | 22 | Std 3-stage mast | in | 98.6 | mm | 2505 |
| | Overall Width | 23 | | in | 43.9 | mm | 1115 |
| | Overhead Guard Height | 24 | | in | 83.5 | mm | 2120 |
| | Turning Radius | 25 | Minimum outside | in | 81.9 | mm | 2080 |
| | Fork Overhang | 26 | Std 3-stage mast | in | 18.5 | mm | 469 |
| | Right Angle Stack | 27 | Includes load length and clearance | in | 147.6 | mm | 3750 |
| | Ground Clearance | 28 | Loaded below mast | in | 3.5 | mm | 90 |
| | | 29 | Center of wheelbase | in | 3.9 | mm | 100 |
| | | | | | | | |
| | Performance | Travel Speed | 30 | Loaded/Unloaded | mph | 10.6/10.6 | km/h |
| Lift Speed | | 31 | Loaded/Unloaded | fpm | 101/105 | mm/s | 505/525 |
| Lower Speed | | 32 | Loaded/Unloaded | fpm | 86/76 | mm/s | 430/380 |
| Max.Drawbar Pull | | 33 | Loaded | lbs | 5280 | kg | 2400 |
| Max.Gradeability | | 34 | Loaded/Unloaded | % | 24/25 | | |
| Systems | Brakes | 35 | Service | Foot/Hyd | | | |
| | | 36 | Parking | Hand/Mech | | | |
| | Engine | 37 | Manufacturer | Kubota | | | |
| | | 38 | Model | WJ2503-L-E3 | | | |
| | | 39 | Emission compliance | EU Stage V/EPA | | | |
| | | 40 | Cylinders | 4 | | | |
| | | 41 | Displacement | L | 2.491 | | |
| | | 42 | Rated power | Hp/rpm | 55.3/2,600 | kW/rpm | 41.3/2,600 |
| | | 43 | Max.torque | N-m/rpm | 175/1,200 | | |

