

**LIUGONG**

# CLG2035G

C

**POWER TYPE**  
Gas/LPG

**BASE CAPACITY**  
@RATED LOAD CENTER  
7,000 LBS/3,500 KG

**LOAD CENTER**  
24 IN/500 MM

**SERVICE WEIGHT**  
10,450 LBS/4,750 KG



# CLG2035G SPECIFICATIONS >>>

GENERAL	Model				CLG2035G		
	Power Type	1			Gas/LPG		
	Units	2		Imperial		Metric	
	Base Capacity	3	@Rated load center	lbs	7,000	kg	3,500
	Load Center	4		in	24	mm	500
WEIGHTS	Service Weight	5	Unloaded	lbs	10,450	kg	4,750
	Axle Load	6	Loaded/Unloaded,Front	lbs	15,880/3,744	kg	7,218/1,702
		7	Loaded/Unloaded,Rear	lbs	2,270/6,706	kg	1,032/3,048
TIRES	Tire Type	8			Pneumatic		
	Wheels	9	Front/Rear		2/2		
	Wheelbase	10		in	66.9	mm	1700
		11	Front		28x9-15-14PR		
	12	Rear		6.50-10-10PR			
	Tread Width	13	Front/Rear	in	39.4/38.8	mm	1000/985
MAST	Max.Fork Height	14	With std 2-stage mast	in	118.1	mm	3,000
	Free lift	15	With std 2-stage mast	in	5.7	mm	145
	Height,Upright Lowered	16	With std 2-stage mast	in	84.6	mm	2,150
	Height,Upright Extended	17	With std 2-stage mast	in	164.6	mm	4,182
	Mast Tilt,Fwd/Back	18	With std 2-stage mast	deg	6°/12°		
	Carriage	19	Width	in	43.3	mm	1,100
	Fork Spread	20	Minimum/Maximum	in	9.6/42.2	mm	244/1,072
	Fork Dimensions	21	TxWxL	in	1.6x4.8x42.1	mm	45x122x1,070
CHASSIS	Length to Fork Face	22	With std 2-stage mast	in	107.8	mm	2,738
	Overall Width	23		in	48.2	mm	1,225
	Overhead Guard Height	24		in	86.6	mm	2,200
	Turning Radius	25	Minimum outside	in	95.9	mm	2,435
	Fork Overhang	26	With std 2-stage mast	in	18.9	mm	480
	Right Angle Stack	27	Includes load length and clearance	in	162	mm	4,115
	Ground Clearance	28	Loaded below mast	in	5.1	mm	130
29		Center of wheelbase	in	6.5	mm	165	
PERFORMANCE	Travel Speed	30	Loaded/Unloaded	mph	11.5/11.8	km/h	18.5/19
	Lift Speed	31	Loaded/Unloaded	fpm	110/114	mm/s	550/570
	Lower Speed	32	Loaded/Unloaded	fpm	101/83	mm/s	505/415
	Max.Drawbar Pull	33	Loaded	lbs	4,620	kg	2,100
	Max.Gradeability	34	Loaded/Unloaded	%	20/23		
SYSTEMS	Brakes	35	Service	Foot/Hyd			
		36	Parking	Hand/Mech			
	Engine	37	Manufacturer	Kubota			
		38	Model	WJ2503-L-E3			
		39	Emission compliance	EU Stage V/EPA			
		40	Cylinders	4			
		41	Displacement	Liters	2.491		
		42	Rated power	Hp/rpm	55.3/2,600	kW/rpm	41.3/2,600
		43	Max.torque	N-m/rpm	175/1,200(LPG)	167.6/1,800(GAS)	

