

CLG2020G-C

02

POWER TYPE
LPG

BASE CAPACITY
@RATED LOAD CENTER
4,000 LBS/1,810 KG

LOAD CENTER
24 IN/600 MM

SERVICE WEIGHT
7,898 LBS/3,590 KG



CLG2020G-C SPECIFICATIONS >>>

General	Model	1	CLG2020G-C			
	Power Type	2	LPG			
	Units	3	Imperial		Metric	
	Base Capacity	4	@Rated load center	lbs	4,000	kg
	Load Center	5		in	24	mm
	Service Weight	6	Unloaded	lbs	7898	kg
	Axle Load	7	Loaded/Unloaded,Front	lbs	10584/1295	kg
		8	Loaded/Unloaded,Rear	lbs	3812/4085	kg
	Tire Type	9	Cushion			
	Wheels	10	Front/Rear		2 / 2	
	Wheelbase	11		in	58.5	mm
	Tire Size	12	Front		21x7-15	
		13	Rear		16x5x10-1/2	
	Tread Width	14	Front/Rear	in	35/36.2	mm
	Max.Fork Height	15	Std 3-stage mast	in	185	mm
	Free lift	16	Std 3-stage mast	in	43.3	mm
	Height,Upright Lowered	17	Std 3-stage mast	in	84.6	mm
	Height,Upright Extended	18	Std 3-stage mast	in	228.9	mm
	Mast Tilt,Fwd/Back	19	Std 3-stage mast	°	6 / 6	
	Fork carriage	20	Width	in	36.2	mm
	Fork Spread	21	Minimum/Maximum	in	9.6/36.2	mm
	Fork Dimensions	22	TxWxL	in	1.6 x 4.8 x 42.1	mm
	Length to Fork Face	23	Std 3-stage mast	in	92.1	mm
	Overall Width	24		in	43.3	mm
	Overhead Guard Height	25		in	83.5	mm
	Turning Radius	26	Minimum outside	in	76.8	mm
	Fork Overhang	27	Std 3-stage mast	in	17.3	mm
	Right Angle Stack	28	Includes load length and clearance	in	141.3	mm
	Ground Clearance	29	Loaded below mast	in	3.1	mm
		30	Center of wheelbase	in	3.9	mm
	Travel Speed	31	Loaded/Unloaded	mph	10.6/10.6	km/h
	Lift Speed	32	Loaded/Unloaded	fpm	112/116	mm/s
	Lower Speed	33	Loaded/Unloaded	fpm	90/80	mm/s
	Max.Drawbar Pull	34	Loaded	lbs	4290	kg
	Max.Gradeability	35	Loaded/Unloaded	%	34/31	
	Brakes	36	Service		Foot/Hyd	
		37	Parking		Hand/Mech	
	Engine	38	Manufacturer		Kubota	
		39	Model		WJ2503-L-E3	
		40	Emission compliance		EU Stage V/EPA	
		41	Cylinders		4	
		42	Displacement	L	2.491	
		43	Rated power	Hp/rpm	55.3/2,600	kW/rpm
			Max.torque	N-m/rpm	175/1,200	

