

CLG2020G-C

02

POWER TYPE
LPG

BASE CAPACITY
@RATED LOAD CENTER
4,000 LBS/1,790 KG

LOAD CENTER
24 IN/600 MM

SERVICE WEIGHT
7,975 LBS/3,625 KG



CLG2020G-C SPECIFICATIONS >>>

General	Model				CLG2020G-C		
	Power Type	1			LPG		
	Units	2			Imperial		Metric
	Base Capacity	3	@Rated load center	lbs	4,000	kg	1790
Weights	Load Center	4		in	24	mm	600
	Service Weight	5	Unloaded	lbs	7975	kg	3625
	Axle Load	6	Loaded/Unloaded,Front	lbs	11020/3835	kg	5009/1743
		7	Loaded/Unloaded,Rear	lbs	1355/4140	kg	616/1882
Tires	Tire Type	8				Cushion	
	Wheels	9	Front/Rear			2 / 2	
	Wheelbase	10		in	58.5	mm	1485
	Tire Size	11	Front			21x7-15	
		12	Rear			16x5x10-1/2	
	Tread Width	13	Front/Rear	in	35/36.2	mm	890/920
Mast	Max.Fork Height	14	With std 2-stage mast	in	185	mm	4700
	Free lift	15	With std 2-stage mast	in	46	mm	1170
	Height,Upright Lowered	16	With std 2-stage mast	in	87.2	mm	2215
	Height,Upright Extended	17	With std 2-stage mast	in	227.3	mm	5774
	Mast Tilt,Fwd/Back	18	With std 2-stage mast	deg		6°/5°	
	Carriage	19	Width	in	36.2	mm	920
	Fork Spread	20	Minimum/Maximum	in	9.6/35.6	mm	244/904
	Fork Dimensions	21	TxWxL	in	1.6 x 4.8 x 42.1	mm	40 x 122 x 1070
Chassis	Length to Fork Face	22	With std 2-stage mast	in	92.1	mm	2340
	Overall Width	23		in	43.3	mm	1100
	Overhead Guard Height	24		in	83.5	mm	2120
	Turning Radius	25	Minimum outside	in	78.7	mm	2000
	Fork Overhang	26	With std 2-stage mast	in	17.3	mm	440
	Right Angle Stack	27	Includes load length and clearance	in	141.3	mm	3590
	Ground Clearance	28	Loaded below mast	in	3.1	mm	80
		29	Center of wheelbase	in	3.9	mm	100
	Travel Speed	30	Loaded/Unloaded	mph	10.6/10.6	km/h	17/17
Performance	Lift Speed	31	Loaded/Unloaded	fpm	112/116	mm/s	560/580
	Lower Speed	32	Loaded/Unloaded	fpm	97.6/97.6	mm/s	488/488
	Max.Drawbar Pull	33	Loaded	lbs	4290	kg	1950
	Max.Gradeability	34	Loaded/Unloaded	%		34/31	
Systems	Brakes	35	Service			Foot/Hyd	
		36	Parking			Hand/Mech	
	Engine	37	Manufacturer			Kubota	
		38	Model			WJ2503-L-E3	
		39	Emission compliance			EU Stage V/EPA	
		40	Cylinders			4	
		41	Displacement	Liters		2.491	
		42	Rated power	Hp/rpm	55.3/2,600	kW/rpm	41.3/2,600
		43	Max.torque	N·m/rpm	175/1,200(LPG)	167.6/1,800(GAS)	

